



MAIL STOP PATENT
Attorney Docket No.: 25667

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

DVIR, et al.

Serial No.: 10/647,123

Filed: August 25, 2003

Title: **ARTICLE TRANSFER SYSTEM**

TRANSMITTAL LETTER

Commissioner for Patents
Alexandria, Virginia 22313-1450

Sir:


Submitted herewith for filing in the U.S. Patent and Trademark Office is the following:

- (1) Transmittal Letter
- (2) Request for Priority
- (3) Priority documents No. 156330

Respectfully submitted,

NATH & ASSOCIATES PLLC

By:


Gary M. Nath
Registration No. 26,965
Marvin C. Berkowitz
Registration No. 47,421
Customer No. 20529

Date: November 21, 2003
NATH & ASSOCIATES PLLC
1030 15th Street N.W., 6th Floor
Washington, D.C. 20005
(202)-775-8383
(202)-775-8396 fax
GMN/MCB/lb:Priority.TRANS



MAIL STOP PATENT
Attorney Docket No. 25667

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

DVIR, et al.

Serial No.: 10/647,123

Filed: August 25, 2003

Title: **ARTICLE TRANSFER SYSTEM**

REQUEST FOR PRIORITY UNDER 35 U.S.C. §119

Commissioner of Patents
Alexandria, Virginia 22313-1450

Sir:


In the matter of the above-captioned application, notice is hereby given that the Applicant claims as priority date June 5, 2003, the filing date of the corresponding application filed in ISRAEL, bearing Application Number 156330.

A Certified Copy of the corresponding application is submitted herewith.

Respectfully submitted,

NATH & ASSOCIATES PLLC

Date: November 21, 2003

By: 
Gary M. Nath
Registration No. 26,965
Marvin C. Berkowitz
Registration No. 47,421
Customer No. 20529

NATH & ASSOCIATES PLLC
6TH Floor
1030 15th Street, N.W.
Washington, D.C. 20005
(202)-775-8383
GMN/MCB/lis (Priority)



מדינת ישראל
STATE OF ISRAEL

Ministry of Justice
Patent Office

משרד המשפטים
לשכת הפטנטים

This is to certify that annexed
hereto is a true copy of the
documents as originally
deposited with the patent
application of which
particulars are specified on the
first page of the annex.

זאת לתעודה כי רצופים
בזה העתקים נכונים של
המסמכים שהופקדו
לכתחילה עם הבקשה
לפטנט לפי הפרטים
הרשומים בעמוד הראשון
של הנספח.

08-09-2003
This היום
לשכת
של המשרד
רשם הפטנטים
Commissioner of Patents

נתאשר
Certified

לשימוש הלשכה
For Office Use

מספר: Number	156330
תאריך: Date	05-06-2003
הוקדם/נדחה: Ante/Post-dated	

בקשה לפטנט
Application For Patent

אני, (שם המבקש, מענו ולגבי גוף מאוגדת מקום התאגדותו)
I, (Name and address of applicant, and in case of body corporate-place of incorporation)

נובה מכשירי מדידה בע"מ, חברה ישראלית מויצמן פארק למדע, ת"ד 266, רחובות 76100, ישראל
Nova Measuring Instruments Ltd., Israeli Company of Weizmann Scientific Park, P.O.B. 266, Rehovot 76100, ISRAEL

בעל אמצאה מכח הדין ששמה הוא
Owner, by virtue of Right of Law of an invention the title of which is

מערכת להעברת פרטים

(בעברית)
(Hebrew)

Article transfer system

(באנגלית)
(English)

Hereby apply for a patent to be granted to me in respect thereof.

מבקש בזאת כי ינתן לי עליה פטנט

* בקשת חלוקה * Application of Division		* בקשת פטנט מוסף * Appl. for Patent of Addition		דרישת דין קדימה * Priority Claim		
מבקשת פטנט from application	לבקשה/לפטנט to Patent/Appl.	מספר/סימן Number/Mark	תאריך Date	מדינת האיגוד Convention Country		
No. _____ מס' _____ Dated _____ מיום _____	No. _____ מס' _____ Dated _____ מיום _____					
P.O.A.: filed in case		* יפוי כח: הוגש בעניין עוד יוגש				
C. 144326 REINHOLD COHN AND PARTNERS Patent Attorneys P.O.B. 4060, Tel-Aviv		המען למסירת מסמכים בישראל Address for Service in Israel ריינהולד כהן ושותפיו עורכי פטנטים ת"ד 4060, תל-אביב				
חתימת המבקש Signature of Applicant בשם המבקשים, ריינהולד כהן ושותפיו ע"י: -		<div style="display: flex; justify-content: space-between;"> 2003 שנת June בחודש 4 היום </div> <div style="display: flex; justify-content: space-between;"> Year of This </div>				

לשימוש הלשכה
For Office Use

טופס זה כשהוא מוטבע בחותם לשכת הפטנטים ומושלם במספר ובתאריך ההגשה, הנו אישור להגשת הבקשה שפרטיה רשומים לעיל.
This form, impressed with the Seal of the Patent Office and indicating the number and date of filing, certifies the filing of the application the particulars of which are set out above.

* מחק את המיותר
Delete whatever is inapplicable

מערכת להעברת פרטים

Article transfer system

Nova Measuring Instruments Ltd.

נובה מכשירי מדידה בע"מ

C. 144326

ARTICLE TRANSFER SYSTEM

FIELD OF THE INVENTION

This invention relates to an article transfer system, particularly useful in applications where precise positioning of an article with respect to a processing or metrology tool is required.

5 BACKGROUND OF THE INVENTION

Various applications, such as article inspection and measurements, as well as lithography processing, require precise movement of the article with respect to a processing tool along a vertical axis (Z-axis). For example, in the manufacture of semiconductor devices, as well as testing of circuits on semiconductor wafers, the
10 wafer is typically supported on a stage mounted for a Z-axis movement (Z-stage) and sometimes also for rotation (Z/Theta stage).

U.S. 5,150,040 discloses a dual mode Z/Theta stage for supporting and moving a workpiece, such as a semiconductor wafer, for positioning during testing. The Z/Theta stage has a peripheral four-point elevator drive. The elevating
15 suspension comprises parallel, vertically oriented, rigid lift pins, which bear the weight of a top-plate. The lift pins are located about the periphery of the stage to provide stability of the support. The top plate essentially floats on the lift pins so that virtually no frictional forces are translated to lift pins. The lift pins are elevated together by the force of four matched pin lift levers, crank arms. The crank arms are
20 driven by downward force from a vertically translating air piston, which is in contact with the crank arms. The air piston provides a gentle force moderated by pneumatic pressure, which can moderate the full force of a stepping motor that drives it.

SUMMARY OF THE INVENTION

There is a need in the art to facilitate processing of articles by supporting an article on an article transfer system enabling precise movement of the article along a vertical axis. Here, the term "*processing*" signifies also measurement or inspection
5 of articles.

The system of the present invention has a simple construction allowing precise movement of an article along a vertical axis (Z-axis) within a limited range of distances, and preferably also rotation of the article about the Z-axis.

The main idea of the present invention consists of utilizing a spring
10 suspension arrangement for supporting an article-carrying member. The spring suspension arrangement is formed by two assemblies arranged in a coaxial relationship, one inside the other, wherein the outer assembly is configured to define two spaced-apart parallel planes perpendicular to the vertical axis. The arrangement is such that the first assembly is kept at a fixed position, and the second assembly,
15 which is intended for supporting an article-carrying member, is driven for movement along a vertical axis with respect to the first assembly, while the assemblies are attached to each other by first and second membrane-like members arranged in a spaced-apart parallel relationship along the vertical axis. The vertical movement of the second assembly causes the deformation of the membrane-like members, thereby
20 limiting the movement of the second assembly (and consequently the article-carrying member) by the deformability of membranes.

Thus, according to a broad aspect of the present invention, there is provided a system for controlling an axial movement of an article, the system comprising:

- a support stage assembly;
- 25 - a spring suspension arrangement mounted on said support stage assembly and comprising first and second assemblies arranged in a coaxial relationship one inside the other, the first assembly being attached to said support stage assembly and the second assembly serving for supporting an article-carrying member and being driven for movement along said axis with respect to the
30 first assembly, the outer one of the first and second assemblies being

configured to define two spaced-apart parallel planes perpendicular to said axis, said first and second assemblies being attached to each other by first and second membrane-like members arranged in a spaced-apart parallel relationship along said axis.

5 According to one embodiment of the invention, the outer assembly is composed of at least three spaced-apart pin-like members kept at a fixed position with respect to one another, and the inner assembly is composed of at least one pin-like member. According to another preferred embodiment of the invention, the outer and inner assemblies are configured as cylinders or prisms, of preferably
10 substantially the same height. The inner assembly at its top and bottom is attached to the top and bottom of the outer assembly by said first and second membrane-like members, respectively. The membrane-like members are preferably of annular geometry, and may be clamped to the opposite sides of each of the outer and inner assemblies via clamping rings.

15 According to another aspect of the invention, there is provided a system for controlling movement of an article along at least a vertical axis, the system comprising:

- a support stage assembly;
- a spring suspension arrangement mounted on said support stage assembly and
20 comprising first and second vertically oriented cylindrical assemblies arranged in a coaxial relationship one inside the other, the first assembly being attached to said support stage assembly and the second assembly serving for supporting an article-carrying member and being driven for movement along the vertical axis with respect to the first assembly, the inner cylindrical
25 assembly at its top and bottom being attached to the top and bottom of the outer cylindrical assembly by, respectively, first and second membrane-like members thereby arranged in a spaced-apart parallel relationship along the vertical axis.

According to yet another aspect of the invention, there is provided a system for controlling movement of an article along at least a vertical axis, the system comprising:

- a support stage assembly;
- 5 - a spring suspension arrangement mounted on said support stage assembly and comprising first and second vertically oriented cylindrical assemblies arranged in a coaxial relationship one inside the other, the outer cylindrical assembly being attached to said support stage assembly and the inner cylindrical assembly serving for supporting an article-carrying member and being driven
10 for movement along the vertical axis with respect to the outer assembly, the inner cylindrical assembly at its top and bottom being attached to the top and bottom of the outer cylindrical assembly by, respectively, first and second membrane-like members being thereby arranged in a spaced-apart parallel relationship along the vertical axis,
- 15 - a drive assembly associated with said inner cylindrical assembly and operable to provide said movement thereof.

The article-carrying member mounted on the second assembly may be driven for rotation with respect to said second assembly in a plane perpendicular to said axis of movement of the second assembly. The support stage assembly may be driven for
20 movement in a plane perpendicular to said axis of movement of the second assembly. Considering a disk-like article, the support stage assembly is preferably movable along at least one perpendicular axis for a distance of at least a radius of the article. The system may thus be operable as a Z-Theta-stage, R-Z-Theta-stage or X-Y-Z-Theta-stage.

25 Thus, according to yet another aspects of the invention, there are provided an R-Theta-Z system and an X-Y-Theta-Z system for controlling movement of an article including the above-described spring suspension arrangement.

The system of the present invention has a simple (and low cost) construction, which can be operable by a simple servo-control mechanism and provides for
30 smoothness of the article movement with high precision. These features are of great

importance for such applications as processing/inspection/measurements of semiconductor wafer structures. Generally, the system of the present invention can advantageously be used in optical measurements (precise focusing), electrical measurements (e.g., in four point probe measurements), near field measurements
5 (e.g., eddy current based resistivity measurements), etc.

BRIEF DESCRIPTION OF THE DRAWINGS

In order to understand the invention and to see how it may be carried out in practice, a preferred embodiment will now be described, by way of non-limiting
10 example only, with reference to the accompanying drawings, in which:

Figs. 1A and 1B schematically illustrate the main constructional and operational principles of an article transfer and positioning system according to the invention;

Fig. 2 exemplifies a specific implementation of the system of the present the
15 invention;

Fig. 3 more specifically illustrates a part of the system of Fig. 2 configured to provide rotation of an article supporting element about the Z-axis; and

Figs. 4A and 4B schematically illustrate the construction of a Z-R-Theta-system of the present invention.

20

DETAILED DESCRIPTION OF THE INVENTION

The present invention provides an article transfer and positioning system configured and operable to enable precise movement of the article along a vertical axis (Z-axis), and preferable also rotation about the Z-axis.

25 **Figs. 1A and 1B** schematically illustrate the main constructional and operational principles of a system 10 according to the invention. The system 10 includes such main constructional parts as a support stage assembly 12 and a spring arrangement 11 mounted on the support stage assembly 12. The stage 12 may be

driven for movement in a horizontal plane, presenting the so-called X-Y-stage or alternatively R-Theta stage.

The spring arrangement 11 includes inner and outer assemblies 14A and 14B, wherein one of these assemblies - the outer assembly 14A in the present example - is attached to the stage 12 and define upper and lower horizontal planes P_1 and P_2 . The other assembly - inner assembly 14B in the present example - is attached to the assembly 14A in a manner to be vertically movable with respect to the assembly 14A within a limited range of distances. This is achieved by attaching the assemblies 14A and 14B to each other via two membrane-like members M_1 and M_2 . Thus, driving of the inner assembly 14B for movement along the Z-axis would result in the simultaneous deformation of the membranes M_1 and M_2 (Fig. 1B), the limits of the Z-movement being defined by the deformability of the membranes and their dimensions. As shown in the figure in dashed lines, an article-carrying member 18 is mounted on the inner assembly 14B, and would thus be movable together with the assembly 14B. The membranes are preferably identical and are centered at the central axis CA of the inner assembly 14B.

It should be understood that, alternatively, the same effect could be achieved by attaching the inner assembly 14B to the stage 12, rather than the outer assembly 14A, and driving the outer assembly 14A for movement along the Z-axis in a similar manner.

Driving of the inner assembly 14B (or outer assembly, as the case may be) along the Z-axis can generally be achieved by associating this assembly with any suitable linear driver 20.

It should also be understood that, generally, in order to define the upper and lower planes for the membranes' location (in their non-deformable position), the outer assembly 14A can be formed by at least three spaced-apart members (e.g. rods or struts) N_1 - N_3 , preferably arranged so as to form a regular polygon (equilateral triangle in the present example) that are fixed to the stage 12 and are kept at a fixed position with respect to one another. As for the inner assembly, it may be in the form

of a member (e.g. rod-shaped) N_4 located at the center of this polygon. Preferably, the assemblies **14A** and **14B** are configured as outer and inner prisms or cylinders.

Referring to **Fig. 2**, there is illustrated a specific, but non-limiting, example of implementation of a system **100** according to the invention for use in transferring and positioning of articles. The system **100** is configured as a Z-stage, and preferably also as an R-Theta-stage. The system **100** comprises a spring suspension arrangement **110** mounted on a stage assembly **112**. The stage **112** can be mounted for movement in a horizontal plane along one or two perpendicular axes (X-Y plane), i.e., presents an X-stage.

The spring arrangement **110** is formed by outer and inner cylinder-like assemblies (drums) **114A** and **114B**. The outer drum **114A** is formed with openings, generally at **115**, the provision of which is optional and is aimed at decreasing the weight of the entire construction and also at allowing access to the inner parts of the construction (e.g., for maintenance purposes). The drums **114A** and **114B** are attached to each other by top and bottom membrane-like members M_1 and M_2 (for example made of a stainless steel and having a thickness of 0.5 mm). The membranes M_1 and M_2 have an annular shape and are clamped to the drums by means of clamping rings **117A** and **117B**, respectively, and bolts **119A** and **119B**.

Further provided in the system **100** is a drive assembly **116** configured and operated for providing a movement of the drum **114B** along the Z-axis. In the present example, the drive assembly **116** comprises a mechanical pair formed by a roller bearing **116A** mounted on a central axis (shaft) **CA** of the inner drum **114B** and a wedge element **116B** supporting the bearing **116A** on its inclined surface. A linear motor **116C** is provided being connected to the wedge element **116B** for moving it along the X-axis. Thus, when the wedge **116A** is driven for a back and forward movement along the X-axis, the roller bearing **116B** drives the inner assembly **114B** for movement along the Z-axis. The inner drum **114B** serves for supporting an article holding assembly **118**. In the present example, where measurements/inspection/processing of semiconductor wafers is considered, the wafer supporting assembly **118** includes a chuck unit **120** preferably mounted for

rotation in the horizontal plane. Considering rotation of the chuck carrying a disk-like article (e.g., semiconductor wafer), the stage 112 is movable along the X-axis within the range defined by the radius of the article (of at least the wafer's radius). The system 100 thus presents the Z-R-Theta stage. It should be understood that, generally, the system 100 might utilize X-Y-movement of the stage 112 with and without a rotation of the chuck unit 120.

Fig. 3, which is a cross-sectional view of a part of the system 100, more specifically illustrates the chuck unit 120 mounted on the inner drum 114B. As shown, the chuck unit 120 is mounted on a rotor-part 124A of a motor 124, whose stator-part 124B is attached to the inner drum 114B. As further shown in Figs. 2 and 3, the chuck unit 120 is mounted on a shaft of the rotor-part 124A via a pair of spherical washers 125A (male) and 125B (female) facing each other by their concave and convex surfaces and a bolt 126, e.g. spherical washers DIN 6319 commercially available from Ganter Griff. While mounting the chuck, its precise horizontal positioning can be regulated by displacing the washers with respect to each other.

Reference is now made to Figs. 4A and 4B showing the entire construction of the system 100 being used for supporting an article, e.g., wafer W (300mm diameter). The configuration of the system 100 presents an accurate R-Theta-Z-system that can be operable as an integrated or stand-alone wafer stage platform. In the present example, the system 100 is used for auto-focusing purposes to control the wafer's in-focus position relative to an optical measuring module located above the wafer (not shown).

Wafer W is hold by a buffer unit (frame) 130. The construction and operation of the buffer unit 130 does not form a part of the present invention and therefore need not be specifically described. The preferred implementation of the buffer unit 130 is disclosed in co-pending U.S. application 10/232,384 assigned to the assignee of the present application. The buffer unit 130 is mounted on the stage 112 and associated with a drive mechanism (not shown) to be movable along the Z-axis with respect to the stage 112, and consequently with respect to the chuck unit 120, which is mounted on the inner drum 114B of the spring suspension arrangement. The chuck 120 is

typically provided with openings for vacuum holding of the wafer. Considering the use of such a buffer unit for gripping and holding a wafer (load/unload station), the diameter of the chuck 120 is smaller than the diameter of the wafer. The chuck 120 is movable along the Z-axis (due to the movement of the drum of spring suspension arrangement) within a 1mm-distance at a $0.1\mu\text{m}$ precision, and is 360-degree rotatable. In the present example, also mounted on the stage 112 is an optical system 132 serving as the so-called "notch finder" for identifying a wafer located on the chuck and/or providing angular positioning of the wafer with respect to a processing tool (measurement, inspection, etc. tool).

10 Those skilled in the art will readily appreciate that various modifications and changes can be applied to the embodiments of the invention as hereinbefore described without departing from its scope as defined in and by the appended claims.

CLAIMS:

1. A system for controlling an axial movement of an article, the system comprising:
 - a support stage assembly;
 - 5 - a spring suspension arrangement mounted on said support stage assembly and comprising first and second assemblies arranged in a coaxial relationship one inside the other, the first assembly being attached to said support stage assembly and the second assembly serving for supporting an article-carrying member and being driven for movement along said axis with respect to the
 - 10 first assembly, the outer one of the first and second assemblies being configured to define two spaced-apart parallel planes perpendicular to said axis, said first and second assemblies being attached to each other by first and second membrane-like members arranged in a spaced-apart parallel relationship along said axis.
- 15 2. The system of Claim 1, comprising a drive assembly associated with said first assembly and operable to provide said movement thereof along said axis.
3. The system of Claim 1, wherein said outer assembly is attached to the support stage assembly, and said inner assembly is driven for movement along said axis.
- 20 4. The system of Claim 1, wherein said inner assembly is attached to the support stage assembly, and said outer assembly is driven for movement along said axis.
5. The system of Claim 1, wherein said outer assembly is composed of at least three spaced-apart pin-like members kept at a fixed position with respect to one
- 25 another, and said inner assembly is composed of at least one pin-like member.
6. The system of Claim 5, wherein an arrangement of said at least three fixed members of the outer assembly defines a regular polygon, and the pin-like member of the inner assembly is located substantially at the center of said polygon.

7. The system of Claim 1, wherein the outer and inner assemblies have substantially the same height.
8. The system of Claim 1, wherein said outer and inner assemblies are configured as cylinders or prisms.
- 5 9. The system of Claim 8, wherein the inner assembly at its top and bottom is attached to the top and bottom of the outer assembly by said first and second membrane-like members, respectively.
10. The system of Claim 9, wherein said membrane-like members have substantially annular geometry.
- 10 11. The system of Claim 9, wherein said membrane-like members are clamped to the opposite sides of each of the outer and inner assemblies via clamping rings.
12. The system of Claim 8, wherein said inner assembly is driven for said movement with respect to the outer assembly, said outer assembly being attached to the support stage assembly.
- 15 13. The system of Claim 8, wherein the outer assembly is driven for said movement with respect to the inner assembly, said inner assembly being attached to the support stage assembly.
14. The system of Claim 1, comprising the article-carrying member mounted on the second assembly for rotation with respect to said second assembly, the system
20 being thereby operable as a Z-Theta-system.
15. The system of Claim 1, wherein said support stage assembly is driven for movement in a plane perpendicular to said axis.
16. The system of Claim 14, wherein said support stage assembly is driven for movement in a plane perpendicular to the Z-axis, the system being thereby operable
25 as a Z-R-Theta- system.
17. The system of Claim 16 for use in transfer and positioning of a disk-like article with respect to said axis, wherein the support stage assembly is movable along a perpendicular axis for a distance of at least a radius of the article.
18. The system of Claim 1, wherein the article-carrying member is mounted on a
30 central axis of said second assembly by means of a pair of spherical washers facing

each other by their male and female surfaces, respectively, thereby enabling precise positioning of the article-carrying member in a plane perpendicular to said axis.

19. The system of Claim 2, wherein said drive assembly comprises a mechanical pair formed by a roller bearing mounted on a tapered surface of the wedge element;
5 and a motor operable for moving the wedge element along an axis perpendicular to said axis.

20. A system for controlling movement of an article along at least a vertical axis, the system comprising:

- a support stage assembly;
- 10 - a spring suspension arrangement mounted on said support stage assembly and comprising first and second vertically oriented cylindrical assemblies arranged in a coaxial relationship one inside the other, the first assembly being attached to said support stage assembly and the second assembly serving for supporting an article-carrying member and being driven for movement along
15 the vertical axis with respect to the first assembly, the inner cylindrical assembly at its top and bottom being attached to the top and bottom of the outer cylindrical assembly by, respectively, first and second membrane-like members thereby arranged in a spaced-apart parallel relationship along the vertical axis.

20 21. The system of Claim 20, comprising a drive assembly associated with said second cylindrical assembly and operable to provide said movement thereof along the vertical axis.

22. The system of Claim 20, wherein said support stage assembly is driven for movement along at least one horizontal axis.

25 23. The system of Claim 20, comprising the article-carrying member mounted on said second cylindrical assembly and driven for rotation with respect to said first cylindrical assembly.

24. A system for controlling movement of an article along at least a vertical axis, the system comprising:

- 30 - a support stage assembly;

- a spring suspension arrangement mounted on said support stage assembly and comprising first and second vertically oriented cylindrical assemblies arranged in a coaxial relationship one inside the other, the outer cylindrical assembly being attached to said support stage assembly and the inner cylindrical assembly serving for supporting an article-carrying member and being driven for movement along the vertical axis with respect to the outer assembly, the inner cylindrical assembly at its top and bottom being attached to the top and bottom of the outer cylindrical assembly by, respectively, first and second membrane-like members being thereby arranged in a spaced-apart parallel relationship along the vertical axis,
- a drive assembly associated with said inner cylindrical assembly and operable to provide said movement thereof.

25. An R-Theta-Z system for controlling movement of an article along the Z-axis and in a horizontal plane, the system comprising:

- a support stage assembly driven for movement along a horizontal axis;
- a spring suspension arrangement mounted on said support stage assembly and comprising first and second vertically oriented cylindrical assemblies arranged in a coaxial relationship one inside the other, the first assembly being attached to said support stage assembly, and the second assembly serving for supporting an article-carrying member and being driven for movement along the vertical axis with respect to the first assembly, said article-carrying member being driven for rotation in the horizontal plane, the inner cylindrical assembly at its top and bottom being attached to the top and bottom of the outer cylindrical assembly by, respectively, first and second membrane-like members thereby arranged in a spaced-apart parallel relationship along the vertical axis.

26. An X-Y-Theta-Z system for controlling movement of an article along the Z-axis and in the horizontal X-Y-plane, the system comprising:

- a support stage assembly driven for movement along X-and Y-axes;

a spring suspension arrangement mounted on said support stage assembly and comprising first and second vertically oriented cylindrical assemblies arranged in a coaxial relationship one inside the other, the first assembly being attached to said support stage assembly, and the second assembly serving for supporting an article-carrying member and being driven for movement along the vertical axis with respect to the first assembly, said article-carrying member being driven for rotation in the horizontal plane, the inner cylindrical assembly at its top and bottom being attached to the top and bottom of the outer cylindrical assembly by, respectively, first and second membrane-like members thereby arranged in a spaced-apart parallel relationship along the vertical axis.

For the Applicants,

REINHOLD COHN AND PARTNERS

By:

A handwritten signature in black ink, appearing to be 'J. Cohn', written over the 'By:' text.




Fig. 1A





Fig. 1B






Fig. 3




Fig. 4A




Fig. 4B